



P^π1

DioSense Selection Guide

		DioSense M	DioSense NM
			
	Spare Sensor Pt. No.	32000003	35003101
	Sensor Bundle Pt. No.	38000010	35003102
Applications	Process	✓	✓
	Potable Water	✓	✓
	Seawater	✓	✗
Mounting Options	Single Open Flow Cell	✓	✗
	Dual Open Flow Cell	✓	✗
	Triple Open Flow Cell	✓	✗
	Closed Flow Cell	✓	✓
	Autoflush (Flow Cell)	✓	✗
Specifications	Standard Cable Length	5m	2m
	Inbuilt Temperature	✓	✓
	Max. Temperature	50°C	70°C*
	Automatic Temp. Compensation	✓	✓
	Max. Pressure	1 Bar	6 Bar
	Response Time (T ₉₀)	90 secs	<2 secs
	pH Range	1 to 12	4 to 10
	Insensitive to Chlorine	✓	✗
	No Electrolyte Required	✗	✓

*If used with the optional flow regulator max temp is 40°C with an option to 60°C.

Mounting Options



Single Open Flow Cell (DioSense M)
PN:32100001



Double Open Flow Cell (DioSense M
and e.g. chlorite)
PN:32100002



Triple Open Flow Cell (DioSense M and
e.g. chlorite and pH)
PN:32100007



Single Closed Flow Cell (DioSense M)
PN:32100010



Single Closed Flow Cell (DioSense NM)
PN: 35003103

Autoclean Options



Autoflush Cell (DioSense M)
PN:36500001

Options



Flow Regulator (DioSense NM)
PN:37001304